VERTICAL IPI STRING

GEOKON®



APPLICATIONS

OPERATING PRINCIPLE

 The remote, continuous, and
 The

 automatic monitoring of:
 uti

 Lateral deformation in dams
 Me

 and tailings
 to

- The stability of natural slopes, landslides, embankments, and subsea marine sediments
- The stability of slurry walls, sheet piling and tieback walls
- Lateral movements in, around and above tunnels and underground openings



Model 6140-HOIST: Assists in the installation and removal of IPI strings.

The basic principle of operation is the

utilization of MEMS (Micro-Electro-Mechanical Systems) tilt sensors to make accurate measurements of inclination over segments of an inclinometer casing.

The Model 6140 Vertical IPI String consists of a string of Biaxial MEMS tilt sensors, installed in rugged engineered polymer housings. One spring-loaded wheel and two fixed wheels, allow the string to positively engage the grooves of conventional inclinometer casing¹ maintaining azimuth with depth. The entire string is held in tension by attaching a suspension weight from the bottommost sensor and hanging the string from the top of the casing using a suspension cable and support bracket. For longer, heavier IPI strings, the Model 6140-HOIST, with sturdy frame, pulley system, support cable, and cable reel, is available to help facilitate their installation and removal. (The hoist is strongly recommended for strings exceeding 100 sensors.)

Sensors in the inclinometer string are mechanically connected with highstrength aircraft cable assemblies, which are free to pivot about the connection point. Sensors are electrically connected via a common bus cable, while the top-most sensor includes a waterproof connector that allows for easy assembly to the chosen readout device (PC, datalogger, SCADA system, etc.) through a customer-specified readout cable.

Each sensor outputs calibrated tilt (angular degrees) and temperature (degree Celsius) readings, which can be easily imported into MS Excel, or any inclinometer visualization software, without the need to convert raw data into engineering units. 'Fits into 70 mm and 85 mm casing

ADVANTAGES

The Model 6140 Vertical IPI String takes the benefits of MEMS technology (wide angular range, high sensitivity, excellent long-term stability) and integrates it into a robust system that requires minimal assembly and is easy to install. With high spatial resolution (0.5 m or 2 ft), the device is capable of measuring extreme lateral movements. Additionally, the flexible nature of the product allows for installations into deformed casings where traditional IPI systems could not be deployed. The Vertical IPI String is light and compact, making it the ideal choice for remote and difficult to access monitoring locations. The product is fully field-serviceable and the string length can be easily extended or shortened on-site.

DATA ACQUISITION

The Model 6140 Vertical IPI String uses industry standard Modbus® Remote Terminal Unit (RTU) protocol to communicate. It employs an RS-485 (half duplex) electrical interface, recognized for its prevalence, simplicity, and success as a robust, industrial physical layer.

Monitoring can be accomplished using GeoNet Digital Loggers, the Model 8020-38 Addressable Bus Converter, Model 8600 Series Dataloggers, Campbell Scientific Dataloggers, or any other device capable of operating as a Modbus RTU client and having an RS-485 port.

TECHNICAL SPECIFICATIONS			
Range ¹	±90°	Maximum String Length	250 m (1,000 ft.)
Resolution ²	0.00025° (0.004 mm/m)	Standard Sensor Length	0.5 m, 2 ft
Precision ³	±0.0075° (±0.13 mm/m)	Weight, Sensor	0.36 kg (0.8 lb.)
Nonlinearity	$\pm 0.005^\circacross\pm 30^\circrange~(\pm 0.09~mm/m)$	Weight, Suspension Weight	4.5 kg (10 lb.)
Temperature Dependent Uncertainty	±0.001°/°C across ±5° angular range (±0.016 mm/m) ±0.0016°/°C across ±15° angular range (±0.026 mm/m) ±0.0026°/°C across ±30° angular range (±0.042 mm/m)	Materials	316 Stainless Steel, Engineered Polymer
Operating Temperature	-40 °C to 65 °C (-40 °F to 149 °F)	Interface	RS-485
Power Supply Voltage	12 VDC (+0%/–10%) for up to 250 sensors 15 VDC (+0%/–10%) for 251-500 sensors	Protocol	MODBUS
Peak Operating Current ⁴	20 mA ±1 mA	Baud Rate	115,200 bps
Average Operating Current ⁴	5 mA	Acquisition Cycle Time	350mS
Standby Current ⁴	2 mA ±0.1 mA	Temperature Accuracy	±0.5 °C
Maximum Sensors per String⁵	500	Ingress Protection	IP68 to 3 MPa (300 m head water)
Datalogger Sensor Limits	GeoNet ADR: 64 GeoNet DHP: 500 Model 8600: 500	Electrical Cable	Four Conductor, Foil shield, Polyurethane jacket, nominal OD = 7.9 mm

¹Calibrated Range: ±30°

²99% confidence interval (i.e. 99 out of 100 individual readings fall within this tolerance).

³Includes random walk (changes between consecutive readings that have no discernible cause) and seismic noise during testing ⁴Operating and standby current are for each individual sensor in a string.

⁵ Dependant on datalogger used. Consult datalogger manufacturer.

ORDERING INFORMATION

6140-1: Vertical IPI String Top, with Readout Cable connector 6140-0.5M: Vertical IPI String Middle, 0.5 m spacing 6140-2FT: Vertical IPI String Middle, 2 ft. spacing 6140-2: Vertical IPI String Bottom, with Suspension Weight connector 6140-3-1: Suspension Cable, <5 m length 6140-3-2: Suspension Cable, 5 m to 10 m length

6140-3-3: Suspension Cable, 10 m to 20 m length 6140-4: Suspension Weight 6140-5-1: Vertical IPI String Connector Bottom, 0.5 m spacing, for strings with >100 sensors, 1 required per 100 sensors 6140-5-2: Vertical IPI String Connector Bottom, 2 ft spacing, for strings with >100 sensors, 1 required per 100 sensors 6140-6: Sensor Hold 6140-HOIST: Installation/Removal Hoist

6180-2: Suspension Bracket 6180-3-1: Readout Cable, bare leads, <15 m length

6180-3-2: Readout Cable, bare leads, 15 m to 30 m length

6180-3V: Readout Cable, bare leads, >30 m length

*Each string comprises a customer-specified number of 6140 middle sensors and one of each of the following: 6140-1, 6140-2, 6140-3, 6140-4, 6180-2, 6180-3. Strings over 100 sensors require one 6140-5 for every 100 sensors



GeoNet Addressable Data Logger.

COMPATIBLE READOUTS AND DATA LOGGERS 8910 Series: GeoNet Wireless LoRa®

Data Acquisition System 8920, 8930, 8950 Series: GeoNet Cellular, Wi-Fi, and Satellite Network Data Loggers

8940: GeoNet Data Loggers 8600 Series: Multi-Channel Data Loggers

8020-38: Addressable Bus converter



Model 6140 Vertical IPI String

Please note: The Model 6140 is currently Patent Pending.



GEOKON 48 Spencer Street Lebanon, NH 03766 · USA www.geokon.com e: teamsales@geokon.com p: +1.603.448.1562

GEOKON is an ISO 9001:2015 registered company

Not all models are CE approved. Contact LE GEOKON for details.

The GEOKON® logo and word mark are registered trademarks with the United States Patent and Trademark Office. | GEOKON maintains an ongoing policy of design review and reserves the right to amend products and specifications without notice. | The LoRa® Mark is a trademark of Semtech Corporation or its subsidiaries. | LoRaWAN® is a registered trademark of the LoRa Alliance® Modbus is a registered trademark of SCHNEIDER ELECTRIC USA, INC. | All other trademarks are the property of their respective owners.

©GEOKON. All Rights Reserved. | Rev-A.5-05/09/2025