ADDRESSABLE VIBRATING WIRE INTERFACE **GEOKON**®



APPLICATIONS

The Model 8020-30 Addressable Vibrating Wire Interface allows the monitoring of a number of vibrating wire sensors on one common cable, for example where strings of sensors are installed in or on:

- Tiebacks
- Soil nails
- Tunnels
- Bridges
- Pipelines
- Retaining walls

OPERATING PRINCIPLE

Vibrating wire sensors are well known for their long-term stability. The advantage of vibrating wire sensors over more conventional types lies mainly in the sensor output, which is a frequency rather than a voltage, and which can be transmitted over long (> 2000 m) cables without appreciable degradation of the signal caused by variations in cable resistance, which can arise from water penetration, temperature fluctuations, contact resistance or leakage to ground. This factor, coupled with the elegance and ruggedness of GEOKON designs results in sensors which exhibit excellent long-term stability and which are ideally suited for long-term measurements in adverse environments.

The Model 8020-30 Addressable Vibrating Wire Interface expands upon the above mentioned features by incorporating vibrating wire sensors with state of the art signal conditioning and digital addressing to provide a measuring system comprising of up to 100 sensors along one common cable (the maximum number of sensors is determined by overall cable length and power supply: please contact GEOKON for more information).

ADVANTAGES AND LIMITATIONS

The Model 8020-30 Addressable Vibrating Wire Interface is designed to "daisy-chain" vibrating wire sensors on one common 4-conductor cable, which is made possible using the industry standard Modbus® RTU protocol over an RS-485 connection. It is particularly useful in incremental extensometers and other multipoint systems, for reducing lengthy cable runs in applications where sensors are installed in or on linear structures, for example a pipeline with strain gauges, a tunnel with pressure cells or a bridge deck with multilevel settlement sensors. It is also useful for applications where many sensor cables might compromise the effectiveness of a grout or cement bond, for example on a soil nail instrumented with vibrating wire strain gauges.

The system comprises a pre-fabricated trunk cable with cable splitters installed at locations close to the gauge locations. The splitters contain the necessary vibrating wire and thermistor circuitry to excite and read each sensor. Readings are accessed, or designated, by their unique Modbus addresses.

Systems can be configured with sensor cables and trunk cables cut to length and molded at GEOKON, or they can be provided with connectors for assembly in the field (please contact GEOKON for details regarding connector options).

READOUT

Readout is achieved using the FPC-2 Field PC with USB-to-RS-485 Dongle, the 8600 Series Dataloggers or with GEOKON Addressable String Reader software¹.

¹Available for download at www.geokon.com/software

Wireless readout can be accomplished using the GeoNet Wireless Data Hosting System.



A series of Model 4430 Deformation Meters, with Model 8020-30 Addressable Interface, installed as an incremental extensometer.



Model 4675 High Sensitivity Settlement System with Model 8020-30 Addressable Interface, on a concrete wall with exaggerated settlement to illustrate change in elevation.

| VIBRATING WIRE SPECIFICATIONS | | |
|--------------------------------|--|--|
| Range | 400 Hz to 5000 Hz | |
| Frequency Trueness | 0.082 Hz | |
| Frequency Precision | 0.146 Hz (99% Confidence Interval) | |
| Frequency Resolution | 0.002 Hz | |
| Excitation Sweeps | 400 Hz to 4500 Hz 400 Hz to 1200 Hz 800 Hz to 1600Hz 1400 Hz to 3500 Hz 2500 Hz to 5000 Hz | |
| Frequency Measurement Duration | 360 mS | |
| Communication | Modbus RTU over RS-485 @ 115200 bps | |

| THERMISTOR SPECIFICATIONS | | |
|---|--|--|
| Temperature Range | -40 °C to +80 °C | |
| Temperature Accuracy ¹ | ±0.5 °C | |
| Temperature System Accuracy | ±0.75 °C | |
| Temperature Resolution | 14-bit, non-linear, 0.032 °C (worst case @ -40 °C) | |
| I Canada a annun i s far the minter and is an aife a la interchanana bilit. | | |

nly and is specified as interc

| MECHANICAL SPECIFICATIONS | |
|---------------------------|--|
| Cable | 2-250P4, 4-conductor, 2 twisted pairs, 6.35 mm (±0.25 mm) diameter |
| Housing | Machined PVC Cylinder/Epoxy filled, 73 \times 19 mm (L \times Ø) |
| Maximum Trunk Cable | Depends on number of sensors. Contact GEOKON for details. |

| ELECTRICAL SPECIFICATIONS | |
|---------------------------|--|
| Supply Voltage | 12V ± 20% |
| Supply Current (Idle) | 1.2 mA/sensor |
| Supply Current (Active) | 57 mA MAX (with 50Ω coils)/ 35 mA MAX (with 180Ω coils). Typical peak current is 30 mA and lasts for 100 ms during the excitation sweep. |
| Excitation Voltage | 3.3 V |
| Operating Range | -40 °C to +80 °C |
| | |



GEOKON 48 Spencer Street Lebanon, NH 03766 · USA www.geokon.com e: info@geokon.com p: +1.603.448.1562

GEOKON is an ISO 9001:2015

Ø