
GEONET NETWORK DATA LOGGERS & DATA HOSTING SYSTEM





GeoNet Network Data Loggers + Wireless Data Hosting System with Cloud integration and secure data access

APPLICATIONS

Typical applications include:

- Groundwater monitoring
- Tailings dams
- Mining/slope stability
- Structural monitoring of buildings, bridges, excavations and tunnels
- Historical structures
- Remote transportation and pipeline corridors

INTRODUCTION

GEOKON Model 8920 and 8930 Series Data Loggers offer a high-value, networked data collection option for all GEOKON vibrating wire instruments and digital sensor (MEMS IPI and VW) strings. Each data logger comes from the factory ready for deployment and may commence with data acquisition in minutes.

Sensor data is collected and transferred via an LTE-M cellular* or Wi-Fi network to a secure cloud-based storage platform where it can be accessed through the GEOKON OpenAPI. Industry leading data visualization software, such as Vista Data Vision, or the free GEOKON Agent program can be used with the OpenAPI for data viewing and reporting. Commissioning, billing and configuration are accomplished via the easy to use GEOKON API Portal.

The portal allows users to activate data loggers, change settings, configure sensor channels, and view current data logger status.

The API Portal can be found at api.geokon.com and the GEOKON Agent program can be downloaded at www.geokon.com/software.

Other available models include:
Digital High Power (DHP) data loggers
that are compatible with GEOKON
Digital Addressable MEMS products
and can read up to 250 GEOKON
MEMS sensors or 500 GEOKON Model
6140 Sensors. With custom firmware,
they are also capable of reading nonGEOKON sensors that utilize RS-485
MODBUS communication protocol.

A tilt data logger that combines the functionality of a biaxial tiltmeter and a GeoNet data logger.

Model 8960 Digital Vibrating Wire interfaces can be connected to GeoNet Multi-Channel and Addressable Data Loggers to expand the capacity of the logger. Multiple VW interfaces can be daisy-chained together to bus the data to a single Logger. The bus limit is 32 units or 64 Channels.

*Compatible with all major cellular networks except Verizon

GENERAL SPECIFICATIONS		
Power Supply	Lithium / 5-24V external (DHP models: Internal sealed lead acid (SLA) battery pack, 4V10 Ah / 5-24V external)	
Operating Temperature	-40° C to +85° C (range varies by power source) (TLT model max of +65° C)	
Temperature Accuracy	±0.5° C	
Direct Connection Type	USB	
Data Transmission Interval	8920, 8930: Min: 10 minutes; Max: 24 hours	
Enclosure	Die-cast aluminum	
Dimensions	Refer to the product instruction manual	

VIBRATING WIRE SPECIFICATIONS		
Trueness	0.082 Hz	
Frequency Precision	±0.146 Hz (99% CI)	
Frequency Resolution	±0.002 Hz	
VW Frequency Range	400 – 6,500 Hz	

DIGITAL DATA LOGGER SPECIFICATIONS		
MEMS Sensors Limits per Model	ADR: 64 sensors (90 sensors, with the sensor string powered via external 12 V power supply) DHP: 250 MEMS or 500 Model 6140 MEMS Sensors	
Communication Protocol	RS-485 Modbus	

WI-FI SPECIFICATIONS		
Protocol	IEEE 802.11 b/g/n IEEE 802.11 d	
Band Support	Station Mode: 2.4 GHz, Channel 1-13 Access Point Mode: 2.4 GHz, Channel 1-11	

TILT DATA LOGGER SPECIFICATIONS	
Range ¹	±90°
Resolution ²	0.00025° (0.004 mm/m)
Precision ³	±0.0075° (±0.13 mm/m)
Nonlinearity	±0.005° across ±30° range (±0.09 mm/m)
Temperature Dependent Uncertainty	$\pm 0.001^{\circ}$ across $\pm 5^{\circ}$ angular range (± 0.016 mm/m) $\pm 0.0016^{\circ}$ across $\pm 15^{\circ}$ angular range (± 0.026 mm/m) $\pm 0.0026^{\circ}$ across $\pm 30^{\circ}$ angular range (± 0.042 mm/m)
Axes	2

¹Calibrated Range: ±30°

ACCESSORIES

8900-SOL-10W-BRJ: GeoNet Series
Solar Panel, 10W, unregulated, for
charging through barrel jack connector.
8900-SOL-10W-USB: GeoNet Series
Solar Panel, 10W, unregulated, for
charging through USB port.

CHG-11: AC Charger

COM-169: USB 2.0 A Male to

C Male Cable

SUP-514: Desiccant pack, 10 grams **KIT-GEONET-C:** Accessory Kit, USB-C Cable/Screw Drivers. For 8920 (except 8920-DHP) and 8930 models.

KIT-GEONET-C-T20: Accessory Kit, USB-C Cable, T20 Screwdriver. For 8920-DHP models.

8800-7B: External 12V battery conversion cable, 3 m length, barrel jack connector. **8800-7BV**: As above, customer-

specified cable length.

8020-7-1: Solar Panel, 20W, regulated.
For use with 12V battery. Includes side-of-pole mounts, charge controller, and 4.5 m interconnect cable with battery clips.

AVAILABLE MODELS



8920-LTM-01C-CBL Single-Channel VW LTE-M Cellular Data Logger



8920-LTM-04C-CBL Four-Channel VW LTE-M Cellular Data Logger



8920-LTM-08C-CBL Eight-Channel VW LTE-M Cellular Data Logger



8920-LTM-ADR-CBL Addressable LTE-M Cellular Data Logger



8920-LTM-TLT-CBL Tilt LTE-M Cellular Data Logger



8920-LTM-DHP-CBL Digital High Power LTE-M Cellular Data Logger



8930-01C-CBL Single-Channel VW Wi-Fi Data Logger



8930-04C-CBL Four-Channel VW Wi-Fi Data Logger



8930-08C-CBL Eight-Channel VW Wi-Fi Data Logger



8930-ADR-CBL Addressable Wi-Fi Data Logger



8930-TLT-CBL Tilt Wi-Fi Data Logger









^{*99%} confidence interval (i.e. 99 out of 100 individual readings fall within this tolerance).
*Includes random walk (changes in consecutive readings with no discernible cause) and seismic noise during testing.